

## EKO-P Perspex Type EM Stop



### Features

- EN54-11 approved (Cert No. 653a/01)
- IP67 Waterproof and addressable models available
- Glass appearance maintains operator deterrence
- Positive activation that mimics the feel of breaking glass
- Visible warning flag confirms activation
- Simple key to reset operating element – no broken glass
- No glass elements to break, lose or incorrectly fit during installation
- Complete functional test with every activation
- Extremely attractive, high value look and feel
- Low profile, heavy-duty terminations – Two built-in resistor values

### Product Overview:

The EM stop button is a unique manual call point that mimics the feel of breaking glass whilst offering the user the benefits and environmental advantages of a re-settable operating element.

The EM stop uses a simple yet ingenious patented mechanism which consists of a rigid plastic operating element and an over center spring mechanism. This arrangement provides real action on operation and simulates break glass activation.

An activation indicator drops into view at the top of the window after the button has been operated. The unit is then simply reset with a key and is ready for re-use straight away.

### APPLICATIONS

It is safe for use in areas where glass cannot be used, e.g. food processing plants and swimming/leisure centres.

As the unit can be simply reset it provides an ideal solution for areas that suffer from a high number of false activations such as schools, shopping centres and other public places.

### TECHNICAL SPECIFICATIONS

Current Rating	3 Amps 12-24V DC / 3A 125-250V AC
Low Current Rating	1-100mA 5-12V DC
Housing & Mounting Box Material	Polycarbonate
Electrical Contact Material	Silver Plated Brass
Operating Temperature	-20C to 65C
Installation Terminal Conductor Size	0.5mm - 2.5mm
Colours	Yellow
Mounting	Flush or surface with back box

