

S&S GSW Water Solenoid Valve



Key Features:

- 230VAC, 24VAC or 24VDC Power Input Models Available
- WRAS Approved
- IP65 Rated
- Normally Closed Safety Shutoff
- 1/2" to 2" Screwed Available For This Model

Approvals:



Product Overview:

The S&S Middle East GoldSeal water solenoid valves are normally closed (N/C) and constructed with a durable lead free brass body, two-way inlet and outlet ports.

Part Codes

Part Codes	Voltage	Description
GSW 15/230AC	230VAC	SOL Wras 1/2 NC EPDM
GSW 15/24AC	24VAC	SOL Wras 1/2 NC EPDM
GSW 15/24DC	24VDC	SOL Wras 1/2 NC EPDM
GSW 20/230AC	230VAC	SOL Wras 3/4 NC EPDM
GSW 20/24AC	24VAC	SOL Wras 3/4 NC EPDM
GSW 20/24DC	24VDC	SOL Wras 3/4 NC EPDM
GSW 25/230AC	230VAC	SOL Wras 1 NC EPDM
GSW 25/24AC	24VAC	SOL Wras 1 NC EPDM
GSW 25/24DC	24VDC	SOL Wras 1 NC EPDM
GSW 32/230AC	230VAC	SOL Wras 1.1/4 NC EPDM
GSW 32/24AC	24VAC	SOL Wras 1.1/4 NC EPDM
GSW 32/24DC	24VDC	SOL Wras 1.1/4 NC EPDM
GSW 40/230AC	230VAC	SOL Wras 1.1/2 NC EPDM
GSW 40/24AC	24VAC	SOL Wras 1.1/2 NC EPDM
GSW 40/24DC	24VDC	SOL Wras 1.1/2 NC EPDM
GSW 50/230AC	230VAC	SOL Wras 2 NC EPDM
GSW 50/24AC	24VAC	SOL Wras 2 NC EPDM
GSW 50/24DC	24VDC	SOL Wras 2 NC EPDM