GSV Gas Solenoid Valves



Key Features:

- 230VAC power input
- Normally closed safety shutoff
- UKCA, CE & KIWA approved
- UL Listed Type available (in 120VAC only)
- 1/2" to 2" NPT available for this model (Other sizes also available in other models)
- Zero differential
- 0-5PSI Maximum working pressure
- 1/4" Inlet & outlet ports
- Visual power indication
- Die cast alumium body
- Min temp: 5°F / max temp: 140°F

Product Overview:

The S&S Middle East range of normally closed, electrically operated gas valves provide safety shut down over combustible gas such as natural (Methane) and LP (Liquefied petroleum). Closed when de-energized, open when energized. These valves are suitable for various applications, such as on/off control on water heaters, atmospheric boilers, roof top make up air units, power burners and commercial kitchen ranges. Add manual re-set by incorporating an S&S Middle East controller or emergency shut off button.

Sizes Available:

| Valve Size " (inch) NPT | Part Number | Max. Working Pressure |
|-------------------------|-------------|-----------------------|
| 1/2" | GSV15 | 360mbar |
| 3/4" | GSV20 | 360mbar |
|]" | GSV25 | 360mbar |
| 1-1/4" | GSV32 | 200mbar |
| 1-1/2" | GSV40 | 200mbar |
| 2" | GSV50 | 200mbar |

Mounting Position:

Power LED Indicator:







Metal shoe construction of the diaphragm allows for vertical installation, with less damage from debris and over pressure.



WARNING If the flow is not in the same direction of arrow, valve may not shut off.



Blue LED indicates valve is receiving control voltage and should be in the open position.




GSV Technical Information

Capacity: CFH at Pressure Drop of 1-Inch Water Column

| Size | M3/Per/Hr | CFH | Max Pressure | Size | 230VAC |
|--------|-----------|-------|--------------|--------|--------|
| 1/2" | 6.4 | 226 | 226,014 | 1/2" | 15W |
| 3/4" | 14.8 | 523 | 522,657 | 3/4" | 22W |
| 1" | 16.7 | 590 | 589,755 | 1" | 22W |
| 1-1/4" | 38.5 | 1,360 | 1,369,615 | 1-1/4" | 42W |
| 1-1/2" | 47.1 | 1,663 | 1,663,320 | 1-1/2" | 42W |
| 2" | 66.7 | 2,355 | 2,355,488 | 2" | 50W |

Current Draw:

Dimensions:



| Size | Α | В | С | D | E |
|--------------|------|-------|-------|-------|------|
| 1/2" 3/4" | 15mm | 72mm | 71mm | 115mm | 55mm |
| 3/4" | 20mm | 92mm | 76mm | 156mm | 59mm |
| 1" | 25mm | 100mm | 80mm | 158mm | 59mm |
| 1-1/4" | 32mm | 149mm | 115mm | 216mm | 71mm |
| 1-1/2" | 40mm | 149mm | 115mm | 216mm | 71mm |
| 2" | 50mm | 170mm | 142mm | 230mm | 76mm |